### (19) World Intellectual Property Organization

International Bureau



## 

### (43) International Publication Date 15 September 2005 (15.09.2005)

**PCT** 

# (10) International Publication Number WO 2005/085775 A1

(51) International Patent Classification<sup>7</sup>: G01F 25/00

(21) International Application Number:

PCT/US2004/003824

- (22) International Filing Date: 6 February 2004 (06.02.2004)
- (25) Filing Language:

English

(26) Publication Language:

English


- (71) Applicants (for all designated States except US): SEY-ONIC S.A. [CH/CH]; Puits-Godet 12, CH-2000 Neuchatel (CH). ARTEL INC. [US/US]; 25 Bradley Drive, Westbrook, Maine 04092-2013 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): CURTIS, Richard [US/US]; 76 Wards Hill Road, Gorham, Maine 04038-2547 (US). BOHNSACK, David L. [US/US]; 115 Tufts Road, New Gloucester, ME 04260 (US). BOILLAT, Marc

[CH/CH]; Avenue de Beauregard 35C, CH-2012 Auvernier (CH).

- (74) Agent: VANDENHOFF, Deborah G.; VAN TASSEL & ASSOCIATES, P.O. Box 2928, Bellaire, Texas 77402-2928 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

### (54) Title: PIPETTE VERIFICATION DEVICE AND PIPETTE



(57) Abstract: Pipettes, widely used in clinical and pharmaceutical laboratories to transfer small volumes of liquid, are subject to hidden performance degradation and operator error. Pipette performance cannot be accepted without monitoring. The invention concerns a verification device (16) for a pipette with a piston (11) for aspirating then dispensing, using a shaft (13), a determined volume of liquid. This device essentially includes: first means for supplying a displaced volume measurement, comparing this measurement to a desired value and generating an indication of the difference between the measured volume and said desired value; and second means, responding to the said first means, for delivering an information relating to said indication.

## WO 2005/085775 A1

GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

#### **Published:**

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.